

CLAIMS

- Sub
A1
- 5
1. Method for activating a local terminal (7) connectable to a first network (1), characterized by the steps:
- a. a server transmits via a second network (5) an activation code to a local activation module (6) which is connected to the second network (5) on the one hand and to the local terminal on the other hand;
 - b. after receiving the activation code, the activation module activates the terminal.
- 10
2. Method according to claim 1, characterized by the steps:
- a. the activation module also activates a connection between the local terminal and the server, via the first network;
 - b. the server further activates the terminal.
- 15
3. Method according to claim 1, characterized in that the activation code also comprises a message that is sent by the server (2) with the activation code to the activation module (6) and that can be read by the terminal (7), after having been activated by the activation module.
4. Method according to claim 3, characterized in that the message is a notification message.
- Sub
A2
- 20
5. Method according to claim 4, characterized in that the notification message relates to a message that is waiting in the server (2) to be read by the user of the terminal.
6. Method according to claim 5, characterized in that the message waiting in the server (2) is an SMS message.
7. Method according to claim 5, characterized in that the message waiting in the server (2) is an e-mail message.
- 25
8. Method according to claim 3, characterized in that the message is an SMS message.
- Sub
A3
- 30
9. Method for activating a local terminal (7) connectable to a first network (1) whereby a second network (5) passes on to an activation module (6) an identifier of a node via which a server (2) connects to the second network, characterized by the steps:
- a. the activation module records the said identifier;
 - b. the activation module activates the terminal in accordance with the value of the recorded identifier.
10. Method according to claim 9, characterized in that the server (2), for activation of the terminal in a variety of ways, connects to the second network via various nodes,

each with different identifiers.

Sub B5 11. System for activating a local terminal (7) connectable to a first network (1), characterized by a local activation module (6) which is connected to a second network (5) on the one hand and to the local terminal on the other hand, which activation module activates the terminal after receiving an activation code.

12. System according to claim 11, characterized in that the activation module also activates a connection between the local terminal and the server, via the first network, which server further activates the terminal.

Sub A4 13. System according to claim 11, whereby the second network (5) passes on to the said activation module (6) the identifier of the node via which the server (2) connects to the second network, characterized in that the activation module records the said identifier and the activation module activates the terminal in accordance with the value of the recorded identifier.

15 14. System according to claim 13, characterized in that the server (2) comprises means for connecting to the second network via various nodes, each with different identifiers, with the aim of activating the terminal in various ways, in accordance with the value of the identifier recorded by the activation module.

20 15. System according to claim 11, characterized in that the first network and the second network are separate networks.

Sub AS 16. System according to claim 11, characterized in that the first network and the second network are constituted by at least partially the same network.

25 17. System according to claim 11, characterized in that the server (2) comprises means for making connection with an external terminal (12,13) or server and being controlled by that external terminal or server on the basis of control parameters.

18. System according to claim 11 or 17, characterized in that the local terminal (7) controls further devices (11).

19. System according to claim 11 or 17, characterized in that the activation module (6) or server (2) controls the further devices.

30 20. System according to claim 19, characterized in that the activation module (6) and/or the local terminal (7) are integrated within the further devices.

21. System according to claims 18-20, characterized in that the further devices (11) are domestic devices.

22. Server (2), characterized in that it comprises selection means (4) for activation in various ways of a local terminal (7) connected to a first network by connecting to a second network various network nodes (9) each with a different identifier.

Sub 5
23. Server according to claim 22, characterized in that the first network and the second network are separate networks.

24. Server according to claim 22, characterized in that the first network and the second network form are constituted by at least partially the same network.

Sub 10
25. Server according to claim 22, characterized in that it comprises means for making a connection to an external terminal (12,13) or server and being controlled by that external terminal or server on the basis of control parameters.

15
26. Module (6) for making a connection between a terminal (7) and a server (2) via a network (5), characterized by means for receiving an activation code (a) from the server (2) followed by activation of the terminal (7).

27. Module according to claim 26, characterized in that the said means activate the terminal in accordance with the value of the received activation code.

Sub 20
28. Module according to claim 26, characterized in that the value of the received activation code comprises an identifier (CLI) of a network node (9).

29. Module according to claim 26, characterized in that the activation code also comprises a message and the module comprises means for passing on that message to the terminal.

Sub 25
30. Module according to claim 29, characterized in that the message is a notification message that relates to a message stored in the server (2).

31. Module according to claim 29, characterized in that the message is an SMS message.

Sub 30
32. Module according to claim 26, characterized by means for detecting a terminal-status code (d), relating to the status of the terminal (7) and the passing on of that status code via the network (5) to the server (2).

33. Module according to claim 32, characterized in that the status code indicates whether the terminal is active or inactive.

Sub A10
34. Module according to one of the preceding claims 26-33 characterized in that the

module is implemented as hardware.

35. Module according to one of the preceding claims 26-33 characterized in that the module is implemented as software.